

OME

MT64



FITTING INSTRUCTIONS

MT64 Coil Over Strut

WARNING

- ◆ This product must be installed exactly as per these instructions using only the hardware supplied.
- ◆ In the event of damage to any suspension component, contact your nearest authorised ARB stockist. Repairs or modifications to the suspension system components must not be attempted.
- ◆ Do not use this product for any vehicle make or model, other than those specified by ARB.
- ◆ Do not remove labels from suspension components.
- ◆ This product or its fixing must not be modified in any way.
- ◆ The installation of this product may require the use of specialized tools and/or techniques
- ◆ It is recommended that this product is only installed by trained personnel
- ◆ These instructions are correct as at the publication date. ARB Corporation Ltd. cannot be held responsible for the impact of any changes subsequently made by the vehicle manufacturer
- ◆ During installation, it is the duty of the installer to check correct operation/clearances of all components
- ◆ Work safely at all times

Note: These fitting instructions should be read in conjunction with the vehicle workshop manual.

DAMPING ADJUSTMENT

These dampers spring C ring clip will be placed as shown in the image.

Move spring groove to desired position based on recommendation.

Spring can be grooved up with no accessories. This will preload the spring. The preloaded spring will give you more lift. This is at the cost of rebound travel. Please select groove as per your requirement

