Turbine Series - 500FG


FUEL

Specifications:

Dimensions:

Height:	11.45" (29.08 cm)		
Width:	4.15" (10.5 cm) with Bracket 6.5" (16.51 cm)		
Depth:	4.15" (10.5 cm) with Bracket 5.17" (13.13 cm)		
Weight:	4.0 lbs (1.8 kg)		
Ports:	3/4"-16 UNF (SAE J1926)		
Service Clearance (Top): 4.0" (10.16 cm)			
Vacuum Installation Recommended Maximum Pressure: 15 psi (1.03 bar)			
Max Flow Rate: 60 gph (227 lph)			

Create a Part Number



DESCRIPTION

Dimensions:	500FG2	500 Turbine Assy., 2 micron Filter
6.50 165.1	500FG10	500 Turbine Assy., 10 micron Filter
	500FG30	500 Turbine Assy., 30 micron Filter
4.55 115.6 TO SLOT CENTERS	500FG122	500 Turbine Assy., 12VDC Heater, 2 micron Filter
	500FG1210	500 Turbine Assy., 12VDC Heater, 10 micron Filter
	500FG1230	500 Turbine Assy., 12VDC Heater, 30 micron Filter
	500FG242	500 Turbine Assy., 24VDC Heater, 2 micron Filter
5,17	500FG2410	500 Turbine Assy., 24VDC Heater, 10 micron Filter
	500FG2430	500 Turbine Assy., 24VDC Heater, 30 micron Filter
	3001 02430	500 Turbine Assy., 24vbc neater, 50 micron riner
OUTLET PORT		
FG Top		
	= Ø 4.15	
4.00		
4.00 CLEARANCE REGOD FOR ELEMENT REMOVAL		
		PORT FOR OPTIONAL 12 VOLT OR 24 VOLT HEATER FEEDTHRU Ø. 32/MB FASTENERS
	/	
	Ļ	4.55
		TO SLOT CENTERS
		MOUNTING HOLE PATTERN
7.5		
	6 Ere	
		CLEAR CONTAMINANT BOWL

FG Profile

ASSEMBLY


- PORT FOR OPTIONAL WATER SENSOR PROBE



FG Front

PARTS

Turbine - 500FG



	Part #	Description
1A	RK 11-1945 RK23284	T-handle Kit - <i>Includes 1B and 2B</i> <i>Optional -</i> T-handle Vacuum Gauge Kit - <i>For 500FG</i> <i>Assemblies Manufactured After 2002</i>
1B	RK11350	T-handle O-ring
0.4	DV 15070	FOOFO Lid Vit Includes 18 and 08
2A	RK 15078	500FG Lid Kit - Includes 1B and 2B
2B		Lid Gasket - Included in 10A
3A	2010SM-OR 2010TM-OR 2010PM-OR	Replacement Element 2 micron - <i>Includes 1B and 2B</i> Replacement Element 10 micron - <i>Includes 1B and 2B</i> Replacement Element 30 micron - <i>Includes 1B and 2B</i>
4A	RK15438-01 RK15438-02 RK15440-01 RK15440-02	Heater Kit - 12 vdc, 100 watt - <i>Use with 10F</i> Heater Kit - 24 vdc, 100 watt - <i>Use with 10F</i> Heater Kit - 12 vdc, 100 watt - <i>Includes 5C</i> - <i>Use with 10F</i> Heater Kit - 24 vdc, 100 watt - <i>Includes 5C</i> - <i>Use with 10F</i>
5A	RK15441-02 RK 15378	Clamp Bracket Kit - <i>Includes (1) Bolt, (1) Washer, and (1) Nut</i> Clamp Bracket - <i>Bracket Only</i>
5B	RK 11838	Carriage Bolt Kit - Includes (2) Bolt, (2) Washer, and (2) Nut
5C	RK 21067	Heater Feed-thru Kit - <i>Includes 5E</i>
5D	RK 11-1679	Feed-thru Plug Kit - Includes 5E
5E		Feed-thru or Plug O-ring - Included in 10A
6A	RK 15010B	Checkball and Gasket Kit
6B	RK 15010B	Centrifuge and Baffle Kit - <i>Includes 6A and 7A</i>
0D	IIK 15015D	
7A	RK15374	Bowl Gasket - Included in 10A
7B	RK15405	Bowl Kit (2002 to Present) - <i>Includes 7A, 8A and 8B</i> **Bowl has 5/8"-11 drain port
7C	RK 15279-01	Bowl Kit (Before 2002) - <i>Includes 7A and 8B</i> **Bowl has 7/8"-14 drain port
8 A	RK 30476	Self-venting Drain Kit (2002 to Present - Use with 7B)
8B	RK 20126	Bowl Plug Kit
8C	RK 30488	Self-venting Drain Kit (1993-2002 - Use with 7C)
8D	RK 11780	Drain Assembly Kit (Pre-1993 - Use with 7C)
9A	RK 15035	Bowl Ring Kit (FG - Tan) - Includes 7A
9B	RK 15081	Bowl Fasteners (set of 4)
		·

Accessories and Parts Available (Not Shown)

10A	RK 15211	Complete Seal Service Kit - 500 Series Filters
10B	RK11-1969	Vacuum Gauge Kit - 500 Series - Includes Fitting & Gauge
10C	RK33803	WIF Probe Kit - 1/2"-20 UNF (Requires 10E)
10D	RK30880E	WIF Sensor and Light Kit - 1/2"-20 UNF
10E	RK 14329 RK 14321	Water Detection Module - 12 vdc Water Detection Module - 24 vdc
10F	RK 11861 RK 11862	Heater Relay Kit - 12 vdc Heater Relay Kit - 24 vdc

RSL0288_CUT_Turbine-500FG (07/16 Rev A)