

Front Bumper Grille For Ford Ranger Mk6 (2016-)

IVIKO (2010-) Part Number: 28G10F0RA6D

KIT CONTENTS

- 1 x Grille moulding.
- 1 x Set (4) Letter mouldings.
- 1 x set self tapping screws

TECHNICAL HELP

Telephone: Autostyling Truckman Group Ltd +44 (0)1384 485 405

1. REMOVE TOP COVER

Remove 5 x panel fasteners from the engine bay front cover.

Carefully release the clips from the front edge then lift the panel away and set aside.

2. REMOVE CENTRE MOULDING

From behind the front panel, remove 3 x T20 screws retaining the centre moulding.

The moulding will not be required but retain the screws.

PRE-INSTALLATION CHECKS.

Carry out a visual check of the vehicle. Clean areas of bodywork that will come into contact with, or be obscured by the product.

Carry out a functional check and test of the vehicle systems prior to starting the installation, in particular, the areas to be worked on during the course of the installation.





3. ASSEMBLE THE GRILLE

Using the screws supplied, attach the letters to the grill.

Insert the screws from the reverse side taking care not to over-tighten.

4. PREPARATION FOR FITTING

Peel back a little of the backing from one end of the adhesive tape located on the top edge of the grille.

5. ATTACH TO THE VEHICLE

Holding the grille in place on the vehicle, refit the two of the T20 screws which were removed earlier (the centre screw is not used).

Do not overtighten.

6. ASSEMBLE THE GRILLE

Carefully pull the end of the tape backing and peel it off.

Firmly press the top edge of the grille into place.

Refit the engine bay front cover and clips.



Auto Styling Truckman Group Limited, Unit 14 Narrowboat Way, Dudley, DY2 0E2, United Kingdom

Tel: +44 (0)1384 485 405 **Fax:** +44 (0)1384 485 453 **Email:** fitting@autostylinguk.com **Web:** www.autostylinguk.com









MODELS COVERED

Ford Ranger Mk6 (2016-)

These instructions are correct at time of publication only and may be amended without notice. For the latest version contact fitting@autostyling.com or call us on +44 (0)1384 485 405